



MS920P

Wireless Pocket 2D Scanner



**VIBRATION
SUPPORT**

Unitech MS920P is a new generation of wireless 2D barcode scanner that doubles the excellent decoding performance in a pocket-sized enclosure. Thanks to its compact & lightweight design for easy mobility, MS920P allows enterprises to simply scan and transmit 1D and 2D barcode in real time to the host wirelessly or to store scanned data in the built-in memory.

User-friendly operation with a compact size

Featuring convenient single-button scanning design and convenience of wireless technology, MS920P enables users to make barcode data collection easy and efficient. MS920P is easily to carry around. Measuring only 109mm long, 51 mm wide and 28 mm thick, MS920P is small in size and easy to carry around. In addition, running on rechargeable Li-Ion battery, it allows users to operate over 13 hours to work and charge the built-in battery by utilizing a standard USB port or charging cradle. MS920P also equipped with a vibration mode to confirm the reading, it is more flexible for users to use in quiet environment, such as hospital.

Durable and superior performance

MS920P incorporates rugged design with an IP42 environmental sealing against moisture and dust, while also surviving a 1.5M drop to concrete. Combining highly visible 617nm red LED-based aimer with advanced scan engine, it can aim effectively well even in low light environment, yet, still delivers superior performance by capturing data from high density barcodes up to 4 mil resolution. Moreover, the read range of MS920P extends beyond competing scanners by an average of 60 percent.

In additions to offer a 10M operation range via its USB dongle, the simple plug-and-play design of MS920P makes the installation much easier without complicated set-up. Providing class-leading motion tolerance of 4 inches per second, MS920P mini barcode scanner is ideal for streamlining productivity at customer-facing operations such as the point of sale, asset tracking management and healthcare applications.

Features

- Build in high performance 2D engine & decoder to read all standard 1D and 2D codes
- LED, beeps and vibration indicate good scan, connection and power status
- User-friendly operation with a pocket-sized enclosure
- Superior performance scan engine to read damaged, poorly printed, overlaid and colored bar codes
- Support batch mode to ensure no data loss when out-of-range reading
- Equipped with a high capacity battery for more than 13 hours operation of continuous use



MS920P

Wireless Pocket 2D Scanner

Optical & Performance

Optical & Performance	Image Sensor, 752 x 480 pixels
Light Source	Illumination: Highly visible white LED
	Aiming : 617 nm red LED
Max. Resolution	1D codes 0.1 mm (4 mils) 2D codes 0.167 mm (6.6 mils)
Skew Angle	±58 degrees
Pitch Angle Sensor	±86 degrees
Printing Contrast Scale	30%
Motion Tolerance	4 inches per second

Reading Distance (DOF PCS=100%)	Label / DOF	near	far
	Code 39, 4mils	60mm	180mm
	Code 39, 5mils	45mm	225mm
	Code 39, 20mils	60mm	640mm
	Code 39, 40mils	125mm	975mm

	Label / DOF	near	far
	EAN/UPC, 13mils	45mm	410mm

	Label / DOF	near	far
	DataMatrix, 7 mils	65mm	150mm
	DataMatrix, 10 mils	45mm	210mm
	DataMatrix, 15 mils	47mm	310mm

	Label / DOF	near	far
	PDF417, 6.6 mils	50mm	182mm
	PDF417, 10 mils	37mm	275mm
	PDF417, 15 mils	45mm	400mm

* =dependent on width of bar code

Accessories

Battery Pack * 1, Whist Strap, Micro USB to USB Cable, Dongle



Battery Pack Whist Strap USB Cable 1 Slot 5 Slot Dongle



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Functionality

Symbologies

1D: EAN/UPC, GS1 Databar (limited expanded & omni-directional), Code 39, Code 128, UCC/EAN 128, ISBN, ISBT, Interleaved/Matrix/Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen,
2D: Data Matrix, PDF417, Micro PDF 417, Codablock, Maxicode, QR, Aztec
Postal: Australian Post, BPO, Canada Post, Dutch Post, Japan Post, PostNet, Sweden Post
Trigger Mode, Flash Mode, Continuous Mode, Buffer mode
Prefix, Suffix, Code ID, Reformatting Date

Operation Mode

Data Formatting

Electrical

Memory Capacity
Operation Voltage
Current Consumption
Battery Type
Battery Duration
Battery Charging time
Operating Time

2 MBytes, store up to 150,000 of EAN13 codes
DC 3V to 5V
Operation mode: 76.8mA
Rechargeable Lithium-ion battery
1100mAh
Fully charged in 4 hours
Over 13 hours (1 scan / 3 seconds)

Mechanical

Scanner Dimension
Scanner Weight
Switch life

51.4 x 109.3 x 28.1 mm
105.2g (with battery)
10 million time

Environmental

ESD Protection
Mechanical Shock
IP rate
Operating Temperature
Storage Temperature
Relative Humidity

Functional after 8K Contact and 12K Air
1.5m onto concrete (scanner only)
IP42
0°C to 50°C
-30°C to 70°C
95% non-condensing

Communication

Radio Frequency
Range
Host Interface supported

Unlicensed 2.4GHz
10M (Line of Sight)
USB

Regulation Approvals

CE, FCC, BSMI

What comes in the box

MS920 scanner
USB cable (Micro USB)
Battery
Hand strap

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

